

**SDIS 0.4X2.0X60****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

VDE insulated slot-head screwdriver, SDI DIN 7437, ISO 2380/2, drive output acc. to DIN 5264, ISO 2380/1.  
SoftFinish grip

**General ordering data**

|            |                                                                                      |
|------------|--------------------------------------------------------------------------------------|
| Version    | Screwdriver, Blade width (B): 2 mm, Blade length: 60 mm, Blade thickness (A): 0.4 mm |
| Order No.  | <a href="#">2749780000</a>                                                           |
| Type       | SDIS 0.4X2.0X60                                                                      |
| GTIN (EAN) | 4050118896527                                                                        |
| Qty.       | 1 pc(s).                                                                             |

**SDIS 0.4X2.0X60****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|          |        |                 |            |
|----------|--------|-----------------|------------|
| Width    | 164 mm | Width (inches)  | 6.457 inch |
| Length   | 165 mm | Length (inches) | 6.496 inch |
| Diameter | 2 mm   | Net weight      | 40 g       |

**Technical data**

|                        |                                                             |         |          |
|------------------------|-------------------------------------------------------------|---------|----------|
| Description of article | VDE-insulated screwdriver with slotted blade 0.4 x 2.0 x 60 | Version | straight |
|------------------------|-------------------------------------------------------------|---------|----------|

**Screwing tools**

|              |         |                     |        |
|--------------|---------|---------------------|--------|
| Blade length | 60 mm   | Blade thickness (A) | 0.4 mm |
| Blade type   | A       | Blade width (B)     | 2 mm   |
| Form         | Slotted |                     |        |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000158    | ETIM 7.0    | EC000158    |
| ETIM 8.0    | EC000158    | ETIM 9.0    | EC000158    |
| ETIM 10.0   | EC000158    | ECLASS 9.0  | 21-04-04-07 |
| ECLASS 9.1  | 21-04-04-07 | ECLASS 10.0 | 21-04-04-07 |
| ECLASS 11.0 | 21-04-04-07 | ECLASS 12.0 | 21-04-04-07 |
| ECLASS 13.0 | 21-04-04-07 | ECLASS 14.0 | 21-04-04-07 |
| ECLASS 15.0 | 21-04-04-07 |             |             |

**Approvals**

Approvals



Approvals MAMID

[https://mdcop.weidmueller.com/mediadelivery/rendition/900\\_319263/-T1z1mm-S800/](https://mdcop.weidmueller.com/mediadelivery/rendition/900_319263/-T1z1mm-S800/)**Environmental Product Compliance**

|                        |                                      |
|------------------------|--------------------------------------|
| RoHS Compliance Status | Not affected                         |
| REACH SVHC             | Lead 7439-92-1                       |
| SCIP                   | b28ab223-64ec-44cf-adb0-4dd6ebcae141 |

**Downloads**Catalogues [Catalogues in PDF-format](#)